

DELTA PLUS GROUP declares that this product complies with the following regulations :

Identification of the PPE object of the declaration : VV835 - CHEMSAFE VV835

<u>Designation :</u> GLOVE IN NITRILE ON POLYAMIDE LINING - FOAM NITRILE COATING PALM - 35 CM

<u>Colour :</u> Green

<u>Size :</u> 08, 09, 10, 11



<u>Specifications :</u>

Double nitrile coating on polyamide lining. Third rough foam nitrile coating on palm and fingertips. Length: 35 cm. Thickness: 1.15 mm on cuff - 1.30 mm on palm.

The PPE is also identifiable by the following means :

- The product picture
- Each PPE wears the name indicated on this declaration of conformity.
- Each PPE wears the bar code indicated in the annex to this declaration of conformity
- Each PPE wears a batch number. For any further information, just give it to us. Our organization, based on this batch number, allows us to ensure the traceability of the PPE.

EU DECLARATION OF CONFORMITY

This declaration of conformity is issued under the sole responsibility of the manufacturer. The object of the declaration identified above is in conformity with the relevant Union harmonisation legislation: Regulation (EU) 2016/425, with its requirements and with the harmonised standards:

CE REGULATION (EU) 2016/425

EN420:2003+A1:2009 General requirements

5: Dexterity (from 1 to 5)

EN388:2016 Protective gloves against mechanical Risks (Levels obtained on the palm)

- 4: Resistance to abrasion (from 1 to 4)
 - 1: Resistance to cutting (from 1 to 5)
- 2: Resistance to tear (from 1 to 4)
- 1: Resistance to puncture (1 to 4)
- X: Resistance to cutting by sharp objects (TDM EN ISO 13997) (from A to F)



EN ISO 374-1:2016 Protective gloves against dangerous chemicals and micro- organisms - Part 1: Terminology and performance requirements for chemical risks.

B: Type B - Water and air tightness according to EN ISO 374-2:2019. Permeation resistance to at least 3 chemicals at level 2 according to EN16523-1: 2015 (from 1 to 6).

.: Determination of resistance to degradation by chemicals according to EN ISO 374-4: 2019. Part 4: Determination of resistance to degradation by chemicals.

- 2 > 30 mn: Méthanol (A) CAS 67-56-1
- 3 > 60 mn: n-Heptane (J) CAS 142-85-5
- 5 > 240 mn: Sodium hydroxide 40% (K) CAS 1310-73-2
- 2 > 30 mn: Sulphuric acid 96 % (L) CAS 7664-93-9



EN ISO 374-5:2016 Protective gloves against dangerous chemicals and micro-organisms - Part 5: Terminology and performance requirements against micro- organisms risks. .: BACTERIA + FUNGI : Water and air tightness according to EN ISO 374-2:2019.

Category III : PPE for risks that may cause very serious consequences such as death or irreversible damage to health (annex I, Regulation (EU) 2016/425).

0075 - C.T.C. (PARC TONY GARNIER 4 RUE HERMANN FRENKEL 69367 LYON CEDEX 07 FRANCIA) : Notified body which performed the EU Type- examination (module B) and issued EU type-examination certificate: 0075 022 162 07 18 1456

The PPE is subject to the conformity assessment procedure to type based on internal production control plus supervised product checks at random intervals (Module C2) under surveillance of the notified body : 0624 - CENTRO TESSILE COTONIERO E ABB (S.P.A. CENTROCOT PIAZZA S. ANNA, 2 21052 BUSTO ARSIZIO ITALY)

Apt, 25/05/2023

Signed for and on behalf of DELTA PLUS GROUP : David GUIHO Marketing director

<u>ANNEX:</u>

Item details			
Item details	Bar code	COLOUR	SIZE
VV835VE08	3295249202866	Green	08
VV835VE09	3295249202873	Green	09
VV835VE10	3295249202880	Green	10
VV835VE11	3295249202897	Green	11